

m/s Godfrey Hirst Australia Pty Ltd
P O BOX 93
South Geelong VIC 3220 Attn Ms Mandy Chandley

TEST REPORT No. 158666

LABORATORY REF: P158666

CUSTOMER REFERENCE

DESIGNER JET CUT PILE CARPET

Sample description as provided by customer
Mass/unit area **17 oz/yd²**
Construction Details **Tufted** Secondary Backing **Synthetic**
Style **Cut Pile**

Order No. **APL 3A**
Pile Fibre Content **100% NYLON**
Colour **Various**
Pile Height **4.5 mm**

TEST METHOD AS/ISO 9239.1 2003 Reaction To Fire Tests For Floorings Part 1 Determination of the Burning Behaviour Using a Radiant Heat Source. As required by specification C1.10 of the Building Code of Australia.

The test values relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be the sole criterion for assessing the potential fire hazard of the product. Clause 9 of AS/ISO 9239 Part 1.

Conditioning as specified in BS EN 13238.2001

Sample submitted Date **Mar 2015**

Test Date **23 Mar 2015**

ASSEMBLY SYSTEM: DIRECT STICK (Details Below).

The floor covering was directly stuck to the substrate using **ROBERTYS 95** adhesive.

Substrate: Non-Combustible

Substrate - 6mm Fibre Reinforced Cement Board to simulate a Non-Combustible Flooring.

The Holding Torque on Specimen Frame was 2Nm.

Initial Test Specimen 1 Length Direction Critical Radiant Flux **8.8 kW/m²**
Specimen 1 Width Direction Critical Radiant Flux **8.5 kW/m²**
Full tests carried out in the **Width** Direction

SPECIMEN	Width #1	Width #2	Width #3	Mean
Critical Radiant Flux (kW/m ²)	8.5	8.3	8.4	8.4
Smoke Development Rate (%.min)	36	39	43	39

The values quoted below are as required by Specification C1.10 Fire Hazard Properties (Floors) of the Building Code of Australia. The Critical Radiant Flux quoted is the value at Flame-Out/Extinguishment (BCA General Provisions A1.1).

MEAN CRITICAL RADIANT FLUX 8.4 kW/m²

MEAN SMOKE DEVELOPMENT RATE 39 percent-minutes

OBSERVATIONS: The samples shrunk away from the heat source, ignited and burnt a short distance.



M. B. Webb
Technical Manager

DATE: 23 Mar 2015

Performance & Approvals
Testing No. 15393
Accredited for compliance with ISO/IEC 17025.

PAGE 1 of 2

Clause 9 of AS/ISO 9239 Part 1

The values on Page 2 have no relevance to the Code.

1004 04 09

TIME FOR EACH SPECIMEN TO REACH EACH MARKER IN SECONDS

Specimen	50	60	110	160	210	260	310	360	410	460	510	560	610	660	710	760	810	860
1	229	230	283	328	529													
2	226	228	287	382	608													
3	229	231	295	393	548													

TESTS

BURNING CHARACTERISTICS

SMOKE PRODUCTION

Specimen	Burn Length (mm) at Flame Out/ Extinguishment	Time To Burn Out (s)	Maximum Light Attenuation (%)	Smoke Development Rate (%.min)
Initial Test: Length	210	742	19	43
Specimen Tests: Width				
1	232	753	14	36
2	241	739	10	39
3	236	759	22	43
Mean	236	750	15	39



ACCREDITED FOR
**TECHNICAL
COMPETENCE**

M. B. Webb
Technical Manager

DATE: 23 Mar 2015

Performance and Approvals
Testing No. 15393
Accredited for compliance
with ISO/IEC 17025.

The laboratory does not allow the use of this page of the report without the use of page 1.

This page alone has no validity under Clause 9 of AS/ISO 9239 Part 1

2004 04 09 1765 23 March 2015