BILLABONG ASHES



www.dreamtimeflooring.com

TECHNICAE SPECIFICATIONS				
Collection:	On Country Range			
Country of Origin:	Australia	Pile Weight:	576g/m² (17oz)	
Colours:	1 Standard	Backing:	Action Bac®	
Yarn:	100% BCF Yarn Dyed Nylon	Installation Method	: Direct Stick Recommended	
Surface Texture:	Patterned Cut Pile	Notes: Available exclu	usively through Dreamtime Flooring	
Gauge:	47.2/ 10cm (1/12th Gauge)	Туре:	Commercial Carpet Roll	
Total Product Thickne	ss: 7 (+/- 1.0)mm	Roll Width:	1.96	
Pile Height:	4.5 (+/- 1.0)mm	Pattern Repeat:	1.96m (W) x 2.91m (L)	


PERFORMANCE

TECHNICAL SPECIFICATIONS

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings~
Colourfast to light:	(ISO 105-B-02-1994) 5-6
Light Reflectance:	Available on Request
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield [®] Antimicrobial Control
ACCS Rating:	Contract Extra Heavy Duty - 4 Star
Contract Guarantee:	10 Years available on request*
Recommended Adhesive:	Refer to our DT Commercial Adhesive Guide www.dreamtimeflooring.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparent	Cy: Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4 Maximum Points - Certificate
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.
🥂 Gre	en Building (\$\$ Return (200)



\$\$

etter Valu

Council Australia

Declare.