

### TECHNICAL SPECIFICATIONS

|                                 |                           |                             |  |
|---------------------------------|---------------------------|-----------------------------|--|
| <b>Collection:</b>              | On Country Range          | <b>Pile Weight:</b>         | 576g/m <sup>2</sup> (17oz)                       |
| <b>Country of Origin:</b>       | Australia                 | <b>Backing:</b>             | Action Bac®                                      |
| <b>Colours:</b>                 | 1 Standard                | <b>Installation Method:</b> | Direct Stick Recommended                         |
| <b>Yarn:</b>                    | 100% BCF Yarn Dyed Nylon  | <b>Notes:</b>               | Available exclusively through Dreamtime Flooring |
| <b>Surface Texture:</b>         | Patterned Cut Pile        | <b>Type:</b>                | Commercial Carpet Roll                           |
| <b>Gauge:</b>                   | 47.2/ 10cm (1/12th Gauge) | <b>Roll Width:</b>          | 1.96   |
| <b>Total Product Thickness:</b> | 7 (+/- 1.0)mm             | <b>Pattern Repeat:</b>      | 1.96m (W) x 2.71m (L)                            |
| <b>Pile Height:</b>             | 4.5 (+/- 1.0)mm           |                             |  |

### PERFORMANCE

|                                |   |
|--------------------------------|---|
| <b>Anti-Static:</b>            | (AATCC 134) <3.5KV at 21°C & 20% Relative Humidity  |
| <b>Flammability:</b>           | Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings~ (ISO 105-B-02-1994) 5-6 |
| <b>Colourfast to light:</b>    | Available on Request  |
| <b>Light Reflectance:</b>      | Stain Warden®   |
| <b>Stain Resistance:</b>       | Bioshield® Antimicrobial Control  |
| <b>Biocontaminant Control:</b> | Contract Extra Heavy Duty - 4 Star  |
| <b>ACCS Rating:</b>            | 10 Years available on request*  |
| <b>Contract Guarantee:</b>     | Refer to our DT Commercial Adhesive Guide <a href="http://www.dreamtimeflooring.com">www.dreamtimeflooring.com</a>                        |
| <b>Recommended Adhesive:</b>   |   |

### SUSTAINABILITY

|                              |   |
|------------------------------|---|
| <b>PVC Minimisation:</b>     | PVC Free  |
| <b>Indoor Air Quality:</b>   | Green Building Council compliant for VOC emission rate limits   |
| <b>Product Transparency:</b> | Declare Red List Free   |
| <b>Green Star:</b>           | Environmental Certification Scheme (ECS). Level 4 Maximum Points - Certificate  |
| <b>Accreditation:</b>        | Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies. |



Specifications and colourations are subject to manufacturing tolerances. Dreamtime Flooring reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. All Dreamtime Flooring carpets must be installed in accordance with the latest AS2455 and any relevant Dreamtime Carpet Installation Instructions.\*This guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply.