

Total Product Thickness:

Pile Weight:

IMPACT RANGE

www.dreamtimeflooring.com

TECHNICAL SPECIFICATIONS

Collection: Impact Range Country of Origin: Australia 6 Standard Colours: Yarn: 100% Straton Plus® Solution Dyed Nylon Surface Texture: Patterned Loop Pile Gauge: 47.2/10cm (1/12th Gauge)

Product Size: 500mm x 500mm

Backing: Enviro Bac® - Minimum 60% recycled content

Installation Method: 1/4 Turn, Brick or Ashlar

Commercial Carpet Tile Type:

Available Options: † 250mm x 1000mm - Skinny Plank^ Enviro Bac Plus® - Cushion Backed Enviro Bac Lite® - Cushion Backed Easy Grip TM - Adhesive Free Installation

PERFORMANCE

6 (+/- 1.0)mm

 $610 \text{g/m}^2 (17 \text{oz/yd}^2)$

(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity Anti-Static:

CRF 4.5kW/m² †

Flammability: Meets the requirements of the NCC Spec. C1.10 relating to fire hazard properties

flooring in class 2-9 buildings (including health and aged care buildings).

Colourfast to light: 6-7 (Minimum mandatory performance for ACCS:5)

Light Reflectance: Available on Request

Stain Resistance: Stain Warden®

Biocontaminant Control: Bioshield® Antimicrobial Control

ACCS Rating: Contact Extra Heavy & Duty & Stairs #19128 †

Contract Guarantee: 15 Years available on request*

Recommended Adhesive: Refer to our DT Commercial Adhesive Guide www.dreamtimeflooring.com

SUSTAINABILITY

PVC Minimisation: PVC Free

Green Building Council & Green Label Plus complaint for VOC's emission rate limits † Indoor Air Quality:

Declare Red List Free **Product Transparency:**

Environmental Certification Scheme (ECS) Level 4 Green Star:

Maximum Points - Certification #13037 †

Accreditation: Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.













